



**ZEBRA**  
CAPTURE  
YOUR EDGE

# ZD230 4-inch Value Desktop Printer

Get More: Extra Features, Quality Construction, Exceptional Value

Not all printers are created equally, especially basic models. To reduce costs, value printers are often constructed using less expensive components and fewer features. Many fail to perform under more demanding duty cycles, create delays and downtime for repairs, and require replacement after only a few years of use. Instead of conserving budget, customers are left with greater expense and hassle. Zebra does it differently. Meet the exception. The ZD230 desktop printer gives you extra features and reliable operation at an affordable price—both at the point of purchase and across the entire lifecycle. Engineered with Zebra quality, it boasts a dual-wall construction. And, it offers wireless connectivity for networked, remote printing. Built to last for years, the ZD230 provides an outstanding return on your investment.



## Get Printing Quickly

The ZD230 is simple to install and begin printing – right out of the box. Easily replace legacy printers using ZPL, EPL or non-Zebra command languages. USB, Ethernet, Wi-Fi and Bluetooth® connectivity options enable universal interoperability. The ZD230 can accommodate a 300 M ribbon roll to lengthen the time between media changes. And, Zebra's OpenACCESS™ clamshell design expedites media replacement. It's also ENERGY STAR® qualified to reduce your operational expenses.

## Just the Features You Need

This 4-inch printer produces labels quickly, up to 6" per second, to keep your workflows moving. Increased memory allows you to store more fonts and graphics. A single LED indicator and single button for feed/pause make it easy to operate and identify printer status. Choose from direct thermal or thermal transfer models, and add an optional factory-installed peeler or cutter. The ZD230 features a core set of Print DNA software applications, powered by Link-OS Basic, to deliver a cost-effective and dependable print experience. It is ideal for use in transportation and logistics, light manufacturing, retail and healthcare applications to print a variety of tickets, tags, passes, labels and receipts.

## Backed by Zebra's Worldwide Service and Support

Access support quickly anywhere around the globe through Zebra's trusted network of more than 10,000 partners. Avoid costly repairs and downtime with an affordable service plan that's tailored to the coverage you need for your desktop printer. Zebra's OneCare SV provides the right level of service at the right price. It gives you two years of coverage for normal wear and tear, double the standard warranty coverage, priority turnaround times at the depot and more—all for a tiny fraction of the cost of a single repair.

## Consistently Exceptional Zebra Certified Supplies

Printing supplies can impact everything from printhead lifespan to operational efficiency. That's why we design, produce and rigorously pretest our own line of thermal printing supplies to ensure consistent, optimized performance in your Zebra printer—and peace of mind for you. For industry-leading quality, service and thermal printing expertise, choose Zebra Certified Supplies.

The ZD230 gives you more. The quality and reliability you expect from Zebra, along with the extra features you need. And, it helps you conserve costs now, and for years to come. Gain your competitive edge with Zebra.



**Get More from Your Investment: Quality, Reliability and Extra Features**  
For more information,  
[visit www.zebra.com/zd230](http://www.zebra.com/zd230)

## ZD230 Specifications

Standard Features	
Thermal Transfer or Direct Thermal print method ZPL and EPL programming languages Single LED status indicator Single button for feed/pause USB connectivity OpenACCESS™ for easy media loading Dual-wall frame construction ENERGY STAR qualified	
Physical Characteristics	
<b>Dimension</b>	Thermal Transfer: 10.5 in. L x 7.75 in. W x 7.5 in. H 267 mm L x 197 mm W x 191 mm H Direct Thermal: 8.6 in. L x 6.9 in. W x 5.9 in. H 220 mm L x 176 mm W x 151 mm H
<b>Weight</b>	2.5 lbs./1.1 kg
Printer Specifications	
<b>Resolution*</b>	203 dpi/8 dots per mm
<b>Memory</b>	256 MB Flash; 128 MB SDRAM
<b>Maximum Print Width</b>	4.09 in./104 mm for 203 dpi
<b>Maximum Print Speed</b>	6 in./152 mm per second
<b>Media Sensors</b>	• Movable black mark sensor, limited range from center to left side • Fixed off-center gap sensor
<b>Firmware</b>	ZPL II; EPL 2; XML

Media and Ribbon Characteristics	
<b>Maximum Label Length</b>	39.0 in./991 mm
<b>Media Width</b>	1.00 in. / 25.4 mm to 4.4 in. / 112 mm
<b>Media Roll Size</b>	5.00 in./127 mm outer diameter Core inner diameter: 0.5 in. (12.7 mm) and 1.0 in. (25.4 mm) standard, 1.5 in. (38.1), 2.0 in., (50.8 mm) and 3.0 in. (76.2 mm) using optional adapters
<b>Thickness</b>	0.003 in. (0.08 mm) min.; 0.0075 in. (.1905 mm) max. (tear-off mode only)
<b>Media Types</b>	Roll-fed or fan-fold, die cut or continuous with or without black mark, tag stock, continuous receipt paper, and wristbands
<b>Ribbon Outside Diameter</b>	2.6 in./ 66 mm (300 m); 1.34 in./ 34 mm (74 m)
<b>Maximum Ribbon Length</b>	984 ft. (300 m)
<b>Ribbon Ratio</b>	• 1:4 media to ribbon (300 m) • 1:1 media to ribbon (74 m)
<b>Ribbon Width</b>	1.33 in./ 33.8 mm ~ 4.3 in./ 109.2 mm
<b>Ribbon Core I.D.</b>	• 300 Meter ribbon 1 in./ 25.4 mm • 74 Meter ribbon 0.5 in./ 12.7 mm

### Ideal for These Applications

#### Light Manufacturing

- Product labeling
- Asset management
- Inventory management
- Work-in-process tracking

#### Transportation and Logistics

- Shipping labels
- Cross docking

#### Retail

- Price labeling
- Receipt printing

#### Healthcare

- Patient identification

## ZD230 Specifications

Operating Characteristics	
Operating Temp.	40° to 105° F/4.4° to 41° C
Storage Temp.	-40° to 140° F/-40° to 60° C
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Electrical	Auto-detectable (PFC Compliant) 100-240VAC, 50-60Hz; ENERGY STAR qualified
Operations and Accessories	
Media Handling	Factory installed peeler or cutter
Communications	<ul style="list-style-type: none"> <li>• Factory-installed USB and Ethernet</li> <li>• Factory-installed USB and Bluetooth 4.1</li> <li>• Factory-installed USB 802.11ac Wi-Fi and Bluetooth 4.1</li> </ul>
Real Time Clock	None
Keyboard Display Unit	No serial port, thus no KDU/ZKDU
Fonts/Graphics/Symbologies	
Bar Code Ratios	2:1 and 3:1
1D Bar Codes	Code 11, Code 39, Code 93, Code 128, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2-or 5-digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar and Planet Code
2D Bar Codes	Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Code, MicroPDF, Aztec

<b>Fonts and Graphics</b>	16 resident expandable ZPL II bitmap fonts Two resident scalable ZPL fonts Five resident expandable EPL2 fonts Native open-type font support Unicode compliant for multi-language, on demand thermal printing China units include SlimSun simplified Chinese font 50 MB user available non-volatile memory, 8 MB user available SDRAM
---------------------------	---

### Printers Supplies

Keep your Zebra printer up and running with genuine Zebra printer supplies, available directly from Zebra.

### Regulatory

- IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus
- CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS, NOM

### Recommended Services

Zebra OneCare SV

### Print DNA Software

This printer features a core set of PrintDNA applications powered by Link-OS Basic.

 **GraphicALL** *één leverancier, altijd de juiste oplossing*

Neon 23, 4751 XA, Oud Gastel

0165-349480 - [info@graphicall.com](mailto:info@graphicall.com) - [www.graphicall.com](http://www.graphicall.com)



NA and Corporate Headquarters  
+1 800 423 0442  
[inquiry4@zebra.com](mailto:inquiry4@zebra.com)

Asia-Pacific Headquarters  
+65 6858 0722  
[contact.apac@zebra.com](mailto:contact.apac@zebra.com)

EMEA Headquarters  
[zebra.com/locations](http://zebra.com/locations)  
[contact.emea@zebra.com](mailto:contact.emea@zebra.com)

Latin America Headquarters  
+1 847 955 2283  
[la.contactme@zebra.com](mailto:la.contactme@zebra.com)